



ITT

NEW!



Rule 1800 GPH HIGH PERFORMANCE 110 VOLT UTILITY PUMP

The new Rule 1800 GPH Utility pump is designed to remove water from hard to reach spaces anywhere water accumulates.

The pump's versatile design makes it the perfect solution to remove water from basements, garages, stairwells, utility rooms, backyards, sumps, pools, pool covers, boats, and for other utility applications. It features an improved unibody housing that is corrosion proof and reduces potential leak paths. The pump features a powerful 1800 GPH motor that only consumes 100 watts, while delivering up to 1800 gallons per hour. Available in non-automatic & automatic versions utilizing standard 110 volt AC current.

Features and Benefits for Model A53S Automatic Pumps

- Computerized automation eliminates need for float switches
- Automatically checks for water every few minutes
- Turns on when only 1" of water is detected
- Never runs dry — Turns off automatically when pumping is complete or if impeller becomes jammed
- Double insulated pump motor is permanently lubricated
- Heavy-duty thermoplastic housing protects pump from the most adverse conditions
- Totally submersible in fresh or salt water
- Snap-off strainer for easy cleaning
- Made in USA with a limited three year warranty



Engineered for life

RULE 1800GPH | HIGH PERFORMANCE UTILITY PUMP

Applications

The Rule line of 1800 GPH utility pumps are ideally suited for removing unwanted water from basements, garages, backyards and boats and has a robust motor, a sturdy housing and a rugged impeller for years of pumping power.

Multiple Uses for Indoor & Outdoor



SUMPS




BASEMENTS



SPA WATER REMOVAL



WATERING GARDEN



CLOGGED DRAINS



POOL COVERS



BOATS



YARD CARE

Specifications

| | FULLY AUTOMATIC | NON-AUTOMATIC |
|-----------------------|---|---|
| Motor | Water Cooled, Permanent Magnet Motor | Water Cooled, Permanent Magnet Motor |
| Volts | 110 A.C. | 110 A.C. |
| Watts | 100 | 100 |
| Housing | Injection Molded Thermoplastic Resin | Injection Molded Thermoplastic Resin |
| Operation | No Switch — Computerized Automation | Non-automatic — Plug It In |
| Shaft | Rust And Corrosion Proof Stainless Steel | Rust And Corrosion Proof Stainless Steel |
| Discharge Connection | 1-1/8" I.D. Hose | 1-1/8" I.D. Hose |
| Accessories | Included Garden Hose Adapter, 90° Elbow Adapter for 1" NPT Pipe | Included Garden Hose Adapter, 90° Elbow Adapter for 1" NPT Pipe |
| Cord | Available in 8 ft or 24 ft. | Available in 8 ft. |
| UPC Code (8 ft cord) | Model A53S: 042237083012 | Model A53D: 042237083463 |
| UPC Code (24 ft cord) | Model A53S-24: 042237083036 | Not Available |



Engineered for life

www.rule-industries.com

USA

ITT Corporation
Cape Ann Industrial Park
Gloucester, MA 01930
Tel: (978) 281-0440
Fax: (978) 283-2619

UK

ITT Industries
Bingley Road, Hoddesdon
Hertfordshire EN11 0BU
Tel: +44 (0) 1992 450145
Fax: +44 (0) 1992 467132

GERMANY

ITT Corporation
Oststrasse 28
22844 Norderstedt
Tel: +49-40-53 53 73-0
Fax: +49-40-53 53 73-11

JAPAN

NHK Jabsco Company Ltd.
3-21-10, Shin-Yokohama
Kohoku-Ku, Yokohama, 222-0033
Tel: +81-045-475-8906
Fax: +81-045-477-1162

ITALY

ITT Corporation
Via Tommaseo, 6
20059 Vimercate, Milano
Tel: +39 039 685 2323
Fax: +39 039 666 307

Warranty: All products of the company are sold and all services of the company are offered subject to the company's warranty and terms and conditions of sale, copies of which will be furnished upon request. The information provided herein is for guidance only, it does not constitute a guarantee of the performance or specification of any individual product or component.