

2655 Napa Valley Corp. Dr., Napa, CA 94558  
(707) 226-8600 FAX: (707) 226-9670  
Date: June, 2008 Rev: 01

Inlet, 50A  
Stainless Steel

Catalog Numbers: 6371EL, 6371EL-B, 6373EL, 6373EL-B

- Item: Stainless steel inlet
- Rating: 50 amperes; 125 volts or 125/250 volts
- Materials: Cap & Bezel are 316 stainless steel.  
Plug body is nylon with CTI greater than 600 volts.  
Contact blades and terminal parts are nickel plated brass.  
Rear enclosure (optional) is glass-filled polyester with UL flammability rating of 94V-0.
- Terminals: Perma-Lock™ self-locking collar-type terminals. Accepts up to 6 AWG wire.
- Enclosure and Strain Relief: Provided on units with "-B."
- Mounting Gasket: Solid Neoprene
- Mounting Screws: Not provided. No. 8 flat or oval head recommended.
- Listings: UL Marine listed, File E57672  
CSA certified, File LR81290  
Complies with ABYC and Coast Guard Standards
- Cap Closure: Cap holds open for easy insertion of shore power cable. Soft Touch design provides for closing with slight pressure. Cap is provided with Easy Lock™ bayonet style locking system. This provides weather seal when used with cords having threaded, or Easy Lock™, sealing rings.

Dimensions:

