



1nm stbd, silver anodized

101-001

1nm stbd, silver anodized
Vertically mounted with 2,5m cable

| Specifications | |
|-----------------------|--|
| Number | 101-001 |
| Light Color | Green |
| Dimensions metric | 92,5 x 28 x 49,7 |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support |
| Intensity | >1.2cd |
| Dimensions imperial | 3.6" x 1.1" x 1.95" |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 1nm |
| Included In Package | 1 Navigation light, precabled with 2.5 meter shielded marine grade cable, Installation guide |
| Operating temperature | -25°C to 55°C |
| Mounting | Vertical |
| Materials | Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 10-32VDC |
| EAN | 5704438008359 |
| IP rating | IP68 |
| Power draw (W) | 1,1 |
| UPC Code | 879343008352 |
| Connection | 2.5m cable |

| Specifications | |
|---|--------------------------|
| Current consumption (mA @ 12VDC) | 66 |
| Stock status | Usually in stock |
| Lead time | 1-2 weeks |
| Current consumption (mA @ 24VDC) | 34 |
| Vessel size | Under 12M |
| Min. feed wire gauge | 0.5mm ² AWG22 |
| Weight (Kg) | 0.39 Kg |
| Weight (Oz) | 13.76 Oz |