



TRIDENT MARINE®

TRIDENT VAC XHD BILGE AND LIVE WELL



149 Series

Trident VAC XHD Bilge and Live Well Hose. Helical PVC reinforcement provides excellent flexibility and bend radius for live well and heavy-duty bilge applications. It has a smooth outer surface to allow for easy clamping. The excellent bend radius of this product gives you the flexibility of a rubber hose making installations a breeze.

Specifications

Construction:

Tube & Cover:
Hard PVC helix

Color: Black

Reinforcement:
PVC Helix

Temperature Range:
10°F-120°F
(-12°C-48°C)

Coils:
100'(30.5m)

Boxed: 50'(15.2m)

Part Number	ID		OD		Working Pressure		Weight		Bend Radius	
	in.	mm.	in.	mm.	Psi Vac In./Hg	Bar	Lb./50 ft.	Kg/ 15.24 M	In	mm
149-0580	5/8	15.9	.855	21.7	28	1.93	10	4.54	1.5	38.1
149-0340	3/4	19.1	.986	25	28	1.93	11	4.99	3	76.2
149-1000	1	25.4	1.254	31.9	28	1.93	15	6.80	3	76.2
149-1180	1-1/8	28.6	1.433	36.4	28	1.93	15	6.80	3	76.2
149-1140	1-1/4	31.8	1.407	35.7	28	1.93	16	7.26	3.5	88.9
149-1120	1-1/2	38.1	1.792	45.5	28	1.93	22	9.98	4	101.6
149-2000-G	2	50.8	2.386	60.6	28	1.93	NA		6.5	165.1

*Burst Pressure is 4 x Working Pressure