



## 1nm Combined sidelight, silver anodized

101-003

1nm comb side, silver anodized  
Horizontally mounted with 2,5m cable

Specifications	
Number	101-003
Light Color	Red,Green
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under Support
Intensity	>1.2cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438009509
IP rating	IP68
Power draw (W)	1,4
UPC Code	879343009502
Connection	2.5m cable

Specifications	
<b>Current consumption (mA @ 12VDC)</b>	87
<b>Current consumption (mA @ 24VDC)</b>	48
<b>Vessel size</b>	Under 12M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	0.62 Kg
<b>Weight (Oz)</b>	21.87 Oz