



## 3nm Masthead/360° White, silver w/FB base

201-021-FB

3nm Masthead/360° White, silver w/FB base  
Horizontal mounted with 0,75m cable

Specifications	
Number	201-021-FB
Light Color	White
Dimensions metric	Ø92,5mm x 36mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Support</a>
Dimensions imperial	Ø3.6" x 1.4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,Installation guide,precabled with 0.75 meter shielded marine grade cable
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438043534
IP rating	IP68
Power draw (W)	3,6
UPC Code	879343043667
Connection	0.7m cable
Current consumption (mA @ 12VDC)	300

**Specifications**

**Current consumption  
(mA @ 24VDC)** 148

**Vessel size** 12-20M

**Min. feed wire gauge** 0.5mm<sup>2</sup> AWG22

**Weight (Kg)** 0 Kg

**Weight (Oz)** 0.00 Oz