



# TracNet™ Coastal Technical Specifications

Stream. Talk. Watch. Connect.


Enjoy faster, smaller, more intelligent communications at sea with a high-powered, single-cable, marinated cellular/Wi-Fi solution with service around the globe.

- As fast as 300 Mbps on the KVH ONE® network
- “2-in-1” hybrid design combining the power of 5G/LTE cellular and Wi-Fi
- Connectivity in the waters where you travel most
- Compact and light with single-cable installation
- All supported by KVH’s premier, 24/7 live KVH OneCare™ service




TracNet Coastal Versions	
TracNet Coastal*	TracNet Coastal Pro
<p>Marina Wi-Fi</p> <p>5G Cellular</p> <p>TracNet Coastal</p> <p>PoE Injector</p>	<p>Marina Wi-Fi</p> <p>5G Cellular</p> <p>TracNet Coastal Pro</p> <p>TracNet Coastal BDU</p>
*User-supplied Wi-Fi access point recommended	

## TracNet Coastal Pro Below Deck Unit (BDU)



## TracNet Coastal Pro Starlink/LEO Configuration



		Specifications	
<b>Antenna Unit</b>			
CELLULAR	Region	Global 5G radio with 4G & 3G fallback	
	Standards	<b>5G NR:</b> 3GPP Release 16 NSA/SA operation, Sub-6 GHz <b>4G LTE:</b> DL Category 19/UL Category 18 <b>3G UMTS:</b> WCDMA	
	Frequency Bands	<b>5G NR SA/NSA:</b> n1/2/3/5/7/8/12/13/14/18/20/25/26/28/29/30/ 38/40/41/48/66/70/71/75/76/77/78/79	
		<b>4G LTE-FDD:</b> B1/2/3/4/5/7/8/12/13/14/17/18/19/20/25/26/28/29/30/32/66/71 <b>4G LTE-TDD:</b> B34/38/39/40/41/42/43/48	
		<b>3G UMTS LAA:</b> B46 <b>3G UMTS WCDMA:</b> B1/ 2/ 4/ 5/ 8/ 9	
	Antenna Gain	<b>617 - 960 MHz:</b> 1.2 dBi ± 1.2 dB	
		<b>1.4 - 3.5 GHz:</b> 2.5 dBi ± 1.5 dB	
		<b>3.5 - 6 GHz:</b> 5.5 dBi ± 3.5 dB	
	Carrier Certifications	T-Mobile / AT&T	
	SIM Technology	Internal KVH eSIM with over-the-air provisioning	
WAN Wi-Fi (Client)	802.11ac 2.4/5 Ghz 2x2 MIMO (Wi-Fi 5)		
GNSS	GPS/GLONASS/BDS/Galileo/QZSS		
Power & Data Cabling	Easy, single-cable install via Category 6a Power over Ethernet (802.3at PoE+)		
Diameter x Height	34.3 cm x 33.3 cm (13.5 in x 13.1 in)		
Weight	3.6 kg (8 lbs)		
Operating Temperature	-25°C to +55°C (-13°F to +131°F)		
Survival Temperature	-30°C to +70°C (-22°F to +158°F)		
<b>Below Deck Unit</b>	<b>TracNet Coastal</b>	<b>TracNet Coastal Pro</b>	
Gigabit Ethernet Ports	1, User LAN only	4, Configurable as Starlink WAN/ Backup WAN/User WAN	
LAN Wi-Fi (Access Point)	N/A	802.11ac 2.4 or 5 Ghz 2x2 MIMO (Wi-Fi 5) Dual-simultaneous WAN & LAN Wi-Fi	
Accessible Micro-SIM Slots	0	2, user-accessible at Below Decks	
Power Input	10-30 Volts DC (direct wire), with available AC Power Supply option		
Power Consumption (Nominal/Max)	10W/14W	16W/22W	
Length x Width x Height	8.0 cm x 8.5 cm x 3.6 cm (3.0 in x 3.3 in x 1.4 in)	20.5 cm x 23.6 cm x 4.4 cm (8.0 in x 9.0 in x 1.7 in)	
Weight	0.23 kg (0.5 lbs)	1.8 kg (4 lbs)	
Operating Temperature	-15°C to +55°C (+5°F to +131°F)		
Survival Temperature	-25°C to +70°C (-13°F to +158°F)		
<b>Complete System</b>	<b>TracNet Coastal</b>	<b>TracNet Coastal Pro</b>	
Intelligent Connection Switching Number of WANs Supported	2 Cell/WAN Wi-Fi	4 Cell/WAN Wi-Fi/Starlink/Backup WAN	
Networking	IPv4/Routing/NAT/DHCP		
Certifications	IEC/EN 60945:2002/COR1:2008 Maritime Equipment IEC/EN 62368-1:2014 Product Safety FCC Part 15 Subpart B, Class B/FCC ID RoHS/REACH		
Warranty	2-years parts, 1-year labor		
KVH Part Number	01-0465-01	01-0465	

Speed and coverage area will vary based on antenna mounting location; onboard network equipment (including hardwired Ethernet connection or belowdeck Wi-Fi access point); position, height of, and distance to cell towers; network congestion; and network type. Service reception may also be affected by environmental or operational conditions, and its uninterrupted availability is not guaranteed.

For more information, visit [kvh.com/coastal](https://kvh.com/coastal) or contact [sales@kvh.com](mailto:sales@kvh.com)